

# VALET

quality products

**ATTUATORE PER CANCELLI SCORREVOLI  
ACTUATOR POUR PORTAIL COULISSANTS  
ACTUATOR FOR SLIDING GATES  
TORANTRIEBE FÜR SCHIEBETORE**

VT. series of operating devices  
created for automatic movement of  
sliding doors and gates weight  
up to : 6000kg



CE



### VT 1500S

<b>Voltage</b>	: 230V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 370W ( 0.5HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 3.2 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 1500 Kgs		

### VT 2000T

<b>Voltage</b>	: 415V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 370W ( 0.5HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 1.3 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 2000 Kgs		

### VT 2500S

<b>Voltage</b>	: 230V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 750W ( 1.0HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 5.6 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 2500 Kgs		

### VT 3000T

<b>Voltage</b>	: 415V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 750W ( 1.0HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 2.1 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 3000 Kgs		

### VT 4000T

<b>Voltage</b>	: 415V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 1.5Kw ( 2.0HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 3.8 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 4000 Kgs		

### VT 5000T

<b>Voltage</b>	: 415V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 2.2Kw ( 3.0HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 5.4 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 5000 Kgs		

### VT 6000T

<b>Voltage</b>	: 415V ± 10%, 50 - 60Hz	<b>Synthetic Oil</b>	: For Life
<b>Power</b>	: 3.0Kw ( 4.0HP )	<b>Protection Rating</b>	: IP 55
<b>Current</b>	: 7.0 Amps	<b>Duty Service</b>	: S1 Continuous Service
<b>Motor Protections</b>	: Thermal bimetallic device	<b>Ventilation</b>	: Bidirectional Fan
<b>Max. Gate Weight</b>	: 6000 Kgs		